



# BULGARKONTROLA

**BULGARKONTROLA SA -Sofia**

*Conformity Assessment Body for Construction Products*

*With identification number 14 and Permit № ПССП-14 on 15.09.2016*

*Issued by Ministry of Regional Development and Public Works*

## CERTIFICATE OF CONFORMITY

**14 – НУРВСНННННН – 3922**

Issued pursuant to Art. 14, par.1 and par. 2 of the Regulation № РД-02-20-1 on 05.02.2015 on the terms and conditions for use of construction products in the construction of the Republic of Bulgaria on Ministry of Regional Development and Public Works for the **construction product**

### **WELDABLE REINFORCING STEEL class B 500 C of bars and of coils**

**used for the reinforcement of concrete with nominal diameter**

and evaluated characteristics in accordance with national requirements as per Supplement № 1 to this Certificate.

placed on the market by

**KROMAN ÇELİK SAN. A.Ş.**

**EMEK MAH. AŞIROĞLU CAD.NO:155 DARICA, KOSCAELI  
TURKEY**

manufactured by

**KROMAN ÇELİK SAN. A.Ş.**

**EMEK MAH. AŞIROĞLU CAD.NO:155 DARICA, KOSCAELI  
TURKEY**

This certificate certifies that the product has been evaluated  
and meets national requirements set out in

**BDS 9252: 2007**

*and item 1.1 of Annex 3 to item 2 of Order № RD-02-14-1329 from 03.12.2015,  
of the Minister of Regional Development and Public Works,  
Amendment and addition by Order № RD-02-14-590 from 05.07.2017*

The Certificate was issued on **19/12/2023**, cancel the Certificate № **14-НУРВСНННННН-3522** from **20/01/2021** and remains valid for three years until **18/12/2026**, provided that the manufacturer ensures consistency of product characteristics and the conditions of production or production control have not been changed significantly.

Place: Sofia

Date: 19/12/2023

Director of "Conformity Assessment" Dept.

*[Signature]*  
/T. Lyubenova/






**Supplement № 1**  
**to Certificate of Conformity № 14- НУРВСПРСБ-3922**

**1. Nominal diameter:**

- Bars with nominal diameter №: 8/10/12/14/16/18/20/22/25/28/32/36/40
- Coils with nominal diameter №: 8/10/12


\* Coils with nominal diameter  $\geq 12$  mm are produced at the request of the client, according to item 8.3 of BDS 9252:2007

**2. Evaluated characteristics in accordance with national requirements**

Characteristics	Requirement to declare / border level
Yield strength, $R_e$	min 500 MPa According tabl. № 4 of BDS 9252:2007
Tensile strength, $R_m$	min 575 MPa According tabl. № 4 of BDS 9252:2007
$R_m / R_e$	min 1,15, max. 1,35 According tabl. № 4 of BDS 9252:2007
Elongation $A_{gt}$ , %	min 7,5 % According tabl. № 4 of BDS 9252:2007
Bending at $180^\circ$	without cracks According tabl. № 4 of BDS 9252:2007
Bending/rebinding, at $90^\circ$	without cracks According tabl. № 4 of BDS 9252:2007
Linear mass, kg / m	$0,395 \div 9,856$ According tabl. № 1 of BDS 9252:2007
Cross-sectional area $A_n$ , mm	$50,3 \div 1256,6$ According tabl. № 1 of BDS 9252:2007
Relative area of the ribs, $f_r$	$6 < d \leq 12$ mm: $f_r$ min.0,040 $d > 12$ mm: $f_r$ min.0,056 According tabl. № 2 of BDS 9252:2007
Profile	 <p>According to figure № 3 of BDS 9252:2007</p>
Fatigue strength, n number of cycles N	$> 2 \cdot 10^6$ According tabl. № 4 of BDS 9252:2007
Chemical composition Weldability (carbon equivalent), $C_{eq}$	max. 0,50 -for the heater max. 0,52 – for the product According tabl. № 3 of BDS 9252:2007

\* Where required

Place: Sofia  
Date: 19/12/2023

Director of "Conformity Assessment" Dept.   
/T. Lyubenova/

